

AMENDMENTS TO THE CLAIMS

1. (Original) An apparatus for the production of synthesis gas including:
 - a reaction vessel;
 - a first heat exchanger, located within one end of said reaction vessel, to heat a preheated oxygen containing stream by indirect heat exchange with an oxygen depleted stream;
 - a second heat exchanger, located within the other end of said reaction vessel, to heat a reactant stream comprising at least one hydrocarbon and steam by indirect heat exchange with a synthesis gas product stream;
 - a plurality of oxygen transport membranes located in a reaction section of the reaction vessel to separate oxygen from the oxygen containing stream, thereby to produce permeated oxygen at anode sides of the oxygen transport membrane tubes, the oxygen transport membranes having cathode sides in communication with the first heat exchanger to receive the oxygen containing stream;
 - the reaction section in communication with the second heat exchanger so that the reactant stream is introduced to the anode side of oxygen transport membranes in said reaction section;
 - a catalyst bed located within the reaction section to promote the reaction of the permeated oxygen in a combination partial oxidation-reforming-water gas shift reaction to produce the synthesis gas product stream;
 - first entrant and discharge passages in communication with the first heat exchanger and second entrant and discharge passages in communication with the second heat exchanger to allow for passage of the oxygen containing and oxygen depleted streams and for passage of the reactant and synthesis gas product streams, respectively, to and from the reactor vessel; and
 - the first heat exchanger, the second heat exchanger, and the oxygen transport membrane tubes each supported within the reactor vessel independently of one another so that each can independently expand or contract.
2. (Original) The apparatus of claim 1, wherein said reactant section has baffle plates configured to produce a flow of the reactant gas through the reactant section and therefore the catalyst bed of one of: axial flow, cross-flow, combined axial and

transverse flow; spiral flow; radially-segmented cross-flow; and transverse-segmented cross-flow.

3. (Original) The apparatus of claim 1, wherein said oxygen transport membranes are tubular and said reactant section has perforated shroud tubes surrounding said oxygen transport membrane tubes.

4. (Original) The apparatus of claim 1, wherein the oxygen transport membranes are formed from oxygen transport membrane tubes; and an inert buffer gas zone is located between the reaction section and seal locations at the open ends of the oxygen transport membrane tubes to allow introduction of a non-reactive gas therein at a pressure greater than that of the reactant zone to prevent leakage of reactant gas from the reactant stream into the oxygen containing stream.

5. (Original) The apparatus of claim 1, wherein each of the first and second heat exchangers has a heat exchanger tubesheet connected to the reactor vessel and a plurality of tubes connected to said tubesheet for internal passage of said synthesis gas product stream and said oxygen containing stream, respectively.

6. (Original) The apparatus of claim 5, wherein said oxygen transport membranes are of tubular configuration having closed and open ends and are supported at their said open ends from a support tubesheet located between the heat exchanger tubesheets.

7. (Original) The apparatus of claim 5, wherein said tubes divide said first and second heat exchangers into oxygen containing gas feed and oxygen depleted gas and feed gas and product gas sides, on opposite sides of said tubes, respectively and said second heat exchanger is configured such that higher mass velocities exist on said feed gas side than on said product gas side.

8. (Original) The apparatus of claim 1, wherein said second heat exchanger has first and second stages with a catalytic pre-reforming section located between said stages containing a pre-reforming catalyst to pre-reform hydrocarbons with more than one carbon molecules to in turn form hydrogen and carbon monoxide therefrom.

9. (Original) The apparatus of claim 1, wherein said reaction section has a catalyst-free section at a location at which said reactant stream enters said reaction section to promote oxidation reactions over reforming reactions, thereby to promote rapid heating of reactant gases in said reactant stream and the oxygen transport ceramic membranes.

10. (Original) The apparatus of claim 1, wherein said catalyst bed has an oxygen transport membrane-free section to define a catalytic equilibrating section.

11. (Original) The apparatus of claim 1, wherein each of the oxygen transport ceramic membranes is of tubular configuration and of composite construction and has a porous support layer located on the anode side and an adjacent dense membrane film located on the cathode side thereof.

12. (Original) The apparatus of claim 11, wherein a reforming catalyst of said catalyst bed is located in an outer portion of said porous support layer.

13. (Original) The apparatus of claim 1, wherein the reaction vessel has an outer jacket to preheat the oxygen containing stream and a passageway communicating between the outer jacket and the first heat exchanger for flow of the oxygen containing stream thereto after having been preheated.

Claims 14-24. (Cancelled)